



## Metalon® Conductive Inks for Printed Electronics

[www.novacentrix.com](http://www.novacentrix.com)

### Metalon® JS-A211

#### Nanosilver Ink – Aqueous dispersion for Inkjet Printing

**JS-A211** is an electrically conductive ink designed to produce circuits on non-porous, temperature-sensitive substrates including polycarbonate, PET, polyimide, and glass. The ink contains a fluoropolymer which provides excellent adhesion and water-resistance on most substrates. The JS-A series of inks are specially formulated for compatibility and stability with various printheads including those manufactured by Dimatix and Xaar. Printing waveforms are available by request.

<b>Performance Properties</b>	<b>Cure temperature (°C)</b>	<b>Cure time (minutes)</b>	<b>Volume Resistivity (Ω-cm)<sup>1</sup></b>	<b>Crosshatch Adhesion</b>	<b>Substrate</b>
	100	60	7.3 x 10E-4	5B	PET
	120	60	2.4 x 10E-4	5B	PET
	140	30	8.6 x 10E-5	5B	PET
	175	10	2.1 x 10E-5	5B	Polyimide
	200	5	1.3 x 10E-5	5B	Polyimide
	250	5	7.7 x 10E-6	5B	Polyimide
	<sup>1</sup> Value calculated based on estimate of 25% porosity of cured print.				
<b>Physical Properties</b>	<b>General Description</b> ..... Water-based Ag ink				
	<b>Flash Point</b> ..... Non-flammable				
		<b>Value</b>	<b>Units</b>		
	Ag content	40	wt%		
	Viscosity	8-12	cP		
	Surface tension	28-32	dyne/cm		
	z-avg particle size <sup>3</sup>	30-50	nm		
Specific gravity	1.6	–			
<sup>3</sup> Malvern dynamic light scattering					
<b>Shipping and Packaging</b>	Standard sample order is 50 mL or multiples of 50 mL. Bulk packaging is also available.				

**[www.novacentrix.com](http://www.novacentrix.com)**  
**Contact us today to learn more.**  
[info@novacentrix.com](mailto:info@novacentrix.com)